ea - Insulator and stud, post type, vertical

DISTRIBUTION (RUS Minimum Requirements)

System voltage, kV	12.5/7.2	12.5/7.2	24.9/14.4		
Leakage, inches	7-1/2	10	15		
Cantilever strength (pounds)	1875	1875	1875		
Flashover, dry, kV	65	70	95		
Flashover, wet, kV	40	50	65		
<u>Lapp</u> 7" Stud 1-3/4" Stud	4415P 4315P	4420P 4320P	4427P 4327P		
Newell Porcelain 7" Stud 1-3/4" Stud	:	43570-7040	47101-7040		
	:	43570-7010	47101-7010		
Porcelain Products (Knox) 7" Stud 1-3/4" Stud	5115-6510	5120-6510	5127-6510		
	5115-6500	5120-6500	5127-6500		
DISTRIBUTION or TRANSMISSION					
ANSI Class	57-2	57-3	57-4		
System voltage, kV	22	34.5	46		
ICB 7" Stud 1-3/4" Stud	- ICB 57-2	- ICB 57-3	- -		
<u>Lapp</u> 7" Stud 1-3/4" Stud	9435 9335	9445 9345	9455 9355		
Newell Porcelain 7" Stud 1-3/4" Stud	37620-7040	41640-7040	41650-7040		
	37620-7010	41640-7010	41650-7010		
Porcelain Products (Knox) 7" Stud 1-3/4" Stud	5135-6512	5145-6512	-		
	5135-6502	5145-6502	-		

U gn - Enclosures, Equipment

Sectionalizing Enclosures

Manufacturer	Catalog No.	
Brooks Utility Products Group	Single Phase 750-7437-001, 750-7437-002, 750-7437-003, 750-7437-004 Three Phase 750-7438-001, 750-7438-002, 750-7438-003, 750-7438-004, 750-7438-005, 750-7438-006, 750-7438-007	
Cooper Power Systems	SecTER Series I and II (Single-Phase and Three-Phase)	
<u>Durham</u>	AMSP() Series	
Highline Products	FSC-32 Single Phase FSC-33 Single Phase FSC-62 Three Phase FSC-55 Three Phase FSC-65 Three Phase FSC-79 Three Phase	
<u>Maysteel</u>	CW200 Series CW300 Series	
Nordic	ND-Series	
Power Design Inc.	Type CJP series, single-phase and three-phase, 15 and 25 kV	
Rough Rider Industries	Series RUF93	
Shallbetter	SPMS Series (dead-front)	

NOTE:

- 1. The above enclosures are available with various multipoint terminations. The owner should specify termination points to be provided.
- 2. These enclosures have been certified as meeting the requirements of ANSI C57.12.28. A copy of the certification is available from the manufacturer.

U gu - Pedestal, Power (Above-Grade) Refer to Construction Drawing UK5

Applicable Specifications: "RUS Specifications for Secondary Power Pedestals," U-6

	Inside Dimensions	Height	
Manufacturer	Inches	Inches	Catalog No.
<u>API</u>	6X6	32	API 6X6
	9X10	25-1/2	API 9 X 10
	10X11	34	API 10 X 11
	10X11	12-1/4	API 10 X FM
	10X11	72	API 10X11XL
	10X14	22-1/2	API 10 X 14
	10X14	26-1/2	API 10 X 14 WB
	16X28	38	API 16X28
	13 Dia.	25	API 176
Coil Sales			
(Charles Industries)	8.25 Dia	31-1/2	CPLP-8
,	8.25 Dia	31-1/2	CPLP-8I(Integral Stake)
	10.75 Dia	31-1/2	CPLP-10
	10.75 Dia	31-1/2	CPLP-10I(Integral Stake)
Electrimold	14.5 x 19.5	31.5	EFSO-111630
Highline Products	14 X 9	31	FSP140931AA
	15.5 X 15.5	30	FSP151530AA
	15.5 X 15.5	36	FSP151536AA
	14 X 9	36	FSP140936AA
	9 X 9	31	FSP090931AA
MacLean (Reliable)	8 x 8	38	UP 8HLP
	8 x 8	46	UP 8HP
	10-1/2 x 10-1/2	26	UP 10HLP
	16-1/2 x 10-1/2	36	UP 1016HLP
	10-1/2 x 10-1/2	42	UP 10HP
Nordic	8 x 8	44	PR-50, PR-55
	9 x 14	30	PR-149 (stake)
			PR-150 (stakeless)
	9 x 14	30	PRMC 150 (low profile)
	9 x 14	24	PRMC-160
	9 x 14	30	PRMC-170 (high profile)
	9 x 14	36	PRMC-190
	9 X 13	30	PSP-91330
	10 X 15	38	PSPF-101538
	15 X 15	30	PSP-151530
	21 X 21	15	PHH-212115
	16 X 19	12	PHH-161912
<u>PenCell</u>	11X14	37	AG-15

U gu - Power Pedestal (Below-Grade) Refer to Drawing UK6

Applicable Specifications: "RUS Specifications for Secondary Power Pedestals," U-6

Manufacturer	Catalog No.
Armorcast	Polymer concrete frame and cover with fiberglass reinforced polyester skirting 6001 Series. P600XXXXA Rotocast Series, molded polyethylene with penta-head bolt
Associated Plastics	Molded polyethylene with galvanized steel or plastic cover Catalog Nos. 1730-1, 3; 1324-1, 3
Blackburn	Molded polyethylene with galvanized steel cover and ground lug. Catalog No. SDR-2PG
Burndy	Molded polyethylene with galvanized steel cover. Catalog No. URD20G23
Carson	Molded polyethylene with plastic cover Catalog No. 1324-12B and 1730-12B H910, HLW1212, H1118, H1324, H1730, H1730, H2436, H3048, HH3060
CDR Systems (Homac)	Fiber reinforced polymer concrete - PA Series with penta-head bolts
Christy Concrete	Polyester reinforced plastic - Series FL8TRCBOX, FL9TRCBOX, FL30TRCBOX, FL36TRCBOX
<u>Dexol</u>	HDPE, DX-101, DX-102 ABS, DX-101HD, DX-102HD
Electrimold	Polymer concrete ring and cover with fiberglass reinforced skirting ECAB series.
	Boxes EPBTH,EPBA series
Highline Products	FHH Series, Fiberglass CHA Series, Fiberglass polymer concrete hybrid
Hubbell (Fargo)	HDPE, B-100R Series ABS, B-200R Series HL51

U ja - Equipment Flat Pad*

Manufacturer	Catalog Number
Armorcast	600 Series, Polymer Concrete P600XXXX Rotocast, LLDPE
Associated Plastics	API 4000 Series RPM
Carolina Dielectrics	Model 0502-1, Fiberglass, Size:40"x44"
CDR Systems (Homac)	PP Series, Fiber reinforced polymer concrete
<u>Diversitech</u>	TP Series - Fiberglass reinforced concrete
Electri-Glass	Fiberglass LP-4145, 41" x 45"
Electrical Materials	Molded HMW Polyethylene Model 64-3BC, 42" x 41" x 4" Model 65-4BC, 52" x46"
Electrimold	EPPT
Highline Products	PBP Series, Polymer concrete hybrid HL-46B, Fiberglass, Size: apprx. 42" X 42"
<u>Formex</u>	Mode1 TP-REA, Molded polyethylene
Heil Rotomold, Inc.	T Series, High density polyethylene
<u>Highline</u>	HL-46B, Fiberglass, Size: approx.42"x42"
Hubbell (Chance)	C107-0162 Fiberglass, Size: 40" x 44"
Major Frame-Crete	ETPP precast, cellular concrete, 42"x42"
<u>Nordic</u>	TP Series, Fiberglass
Parking Bumper Company – a Division of Hog Slat, Inc.	7610, 7612, 7613, 7626PE, 7621
PenCell Plastics	TP-4220, TP-4224, TP-4227
Quality Rubber Company	34242 light-weight concrete
Quazite Corp.	Composolite - PH Series
<u>RMI-D</u>	Dwg. No. 730126-2, Molded polyethylene Size: 42" x 42"
Smith Cattleguard	Easi Set T. Series, Precast Reinforced Concrete
<u>Thermodynamics</u>	Poly-Pad, PR Series, Molded polyethylene YEPR031220, YEPR031226, compression molded polypropylene

^{*}Order by catalog number and size.